

## TECHNICAL DATA SHEET

# KOMPOZIT PRIME

INTERIOR / EXTERIOR ACRYLIC  
GENERAL PURPOSE PRIMER  
1342 SERIES

KOMPOZIT PRIME is a high quality acrylic general use primer/sealer which can be used on interior and exterior surfaces including drywall, wallboard, plaster, masonry concrete, composition board, aluminum, galvanized metal, and wood. Use of this product before topcoating provides an even painting surface which ensures color and sheen uniformity. KOMPOZIT PRIME is a LOW VOC primer and contains no ethylene glycol, crystalline silica, lead, or mercury.

### SURFACE PREPARATION

Ensure that all surfaces are clean prior to painting. Dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust, and all other foreign materials must be removed.

**Mildew:** Remove mildew before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. NOTE: BLEACH MAY DISCOLOR OR DAMAGE EXISTING FINISH. TEST BEFORE TREATING ENTIRE SURFACE. ALTERNATIVE MILDEW SOLUTION MAY BE REQUIRED. Rinse thoroughly with water and allow surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. DO NOT ADD DETERGENTS OR AMMONIA TO THE BLEACH/WATER SOLUTION.

**New Drywall:** Sand all drywall surfaces until smooth. Remove any remaining drywall dust. Allow all drywall compounds to dry completely before coating. Prime with this product.

**New Plaster:** Dry and cure new plaster for at least 30 days prior to painting. Sand smooth. If plaster is soft, porous, or powdery, use mixture of one part vinegar and one part water to neutralize/harden surface. Rinse with water and allow to dry completely. Prime with this product.

**New Wood:** Sand wood surfaces thoroughly to remove mill glaze. Patch holes and imperfections with wood filler, let dry completely and sand. Use a wiping cloth to remove all dust. Use a 100% acrylic, siliconized paintable caulking to fill gaps. Allow to completely dry prior to priming and painting. Prime with this product.

**Weathered Wood:** Strip all loose wood fibers and coatings. Remove mold, mildew, algae and fungus stains. Prime with this product.

**Pressure Treated Wood:** Warning! Sanding or scraping pressure treated lumber may be hazardous. Always wear protective clothing and gear, including gloves and goggles.

**Previously Painted Surfaces:** Remove all loose and peeling paint and any foreign materials. Scrub the surface with a solution of detergent and water to remove any dirt or grease. Rinse the solution off thoroughly. Chalky surfaces may require a separate Acrylic Sealer. Use appropriate spackling to set nails and to fill holes, scratches and gouges. Allow to completely dry and sand until smooth.

**All Glossy Surfaces:** Sand surfaces thoroughly prior to priming and painting. Prime with this product. Test first on hard, slick, or otherwise potentially problematic areas.

**Masonry:** Cure the surface for at least 30 days and check pH to ensure 10.0 or less prior to painting. Test to see if smooth masonry requires a profile to ensure paint adhesion. Create a profile for all other smooth trowel concrete using a muriatic acid etcher, mechanical means or another effective method. Remove all debris prior to priming or painting. Prime with this product.

### KOMPOZIT LIMITED WARRANTY

Kompozit LLC guarantees satisfaction when applied to a properly prepared surface in accordance with the instructions on this document. If not satisfied, contact Kompozit LLC to discuss available remedies. Warranty does not apply to any defect or damage resulting from improper surface preparation or application, structural defects or failure of a previous paint. This warranty is made to the original paint purchaser and is not transferable. Labor or any associated labor costs and any indirect, special, incidental, or consequential damages are excluded from this warranty. Some states do not allow the exclusion or limitation of the incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

[www.kompozitusa.com](http://www.kompozitusa.com)

1033 SW 30th Ave  
Deerfield Beach, FL 33442

Tel: (954) 531-0983

Made in U.S.A.

- Interior / Exterior
- General Use
- Quick dry & recoat
- Low VOC
- Provides uniform painting surface
- Soap and water clean-up

### PRODUCT VALUES:

|  |   |
|--|---|
| Vehicle Type: Acrylic                                | Recommended application temperature: from 50°F-90°F   |
| Viscosity: 100-105 Krebs Units                       | Practical Coverage: Covers approximately 300-400 ft <sup>2</sup> per gallon (27-37 m <sup>2</sup> per 3.78 L) depending on surface porosity |
| Sheen: 0-5 Units 60° angle                           | Do not thin.  |
| Flash point: N/A                                     | Dry Time: @ 77° F:  |
| Volume Solids: 38%                                   | To the touch: 30 minutes  |
| Weight Solids: 50%                                   | Recoat: 2-4 hours   |
| Weight Per Gallon: 10.7 lbs/gal                      | Colors: N/A   |
| Clean-up Solvent: Soap & water                       | Shelf Life: Over 1 year   |
| VOC: Less than 5 g/L                                 |   |
| Recommended Film Thickness: 4.0 mil Wet, 1.5 mil Dry |   |

**Aluminum and Galvanized Steel:** Aluminum and Galvanized Steel: Ensure that all metals are clean prior to painting. Oils, rust, mill scale and other contaminants must be removed. Oil films on new non-ferrous metals should be scrubbed with water and detergent, then rinsed completely. Sanding, abrasion or chemical abrasion is required for optimal adhesion. Prime with this product.

**Ferrous Metals:** Use sandpaper, steel wool, abrasive blasting or other abrading methods to remove all rust and mill scale. Prime with a separate rust-inhibiting primer the same day cleaned to prevent rust.

### APPLICATION



Mix thoroughly before use. Do not thin. May be applied by brush (synthetic), roller (3/8" or larger nap) or spray. Use tip size .015" - .019" and pressure range of 1500 - 2000 psi for airless spray application. Adjust pressure as necessary. If using more than one container of the same color, intermix the containers to ensure uniform color. Determine air, surface and dew point prior to painting. Do not apply when temperatures are below 50°F or when temperatures could drop below 50°F within 48 hours of application. Do not apply if rain or snow is expected within 48 hours. Temperature must be 50°F or higher on large expanses of metal being painted. Check any accompanying primer temperature requirements prior to applying.

**CAUTIONS / LIMITATIONS:** Do not allow paint to freeze. Not for use on floors. Recommended application for temperatures from 50°F - 90°F to ensure proper drying and film formation. Avoid heavy traffic for 24 hours after painting. Do not wash or clean for four weeks to ensure full cure. One year shelf life when unopened.

**CLEAN-UP / DISPOSAL:** Clean paint, associated equipment and skin with warm, soapy water. Keep container closed when not in use. Use original container for storage and disposal. Absorb spills with inert material such as sand or kitty litter. Check and abide by local, state and federal regulations on container and paint disposal.

**WARNING!** This product can cause irritation to the skin and eyes. Always wear protective clothing and gear including gloves, goggles and a face mask. Do not eat, drink or smoke while using this product. Harmful if swallowed. Remove contaminated clothing and wash prior to reusing. Wash hands well after handling. Check and abide by local, state and federal and regulations on paint and associated waste disposal.

**FIRST AID:** Eyes: Use water to gently rinse for several minutes. Remove contacts if necessary and possible. Seek medical attention if irritation persists. Skin: Use soap and water to clean. Swallowed: Rinse mouth and seek medical attention if necessary.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Kompozit Paints assumes no obligation or liability for use of this information. UNLESS KOMPOZIT LLC AGREES OTHERWISE IN WRITING, KOMPOZIT LLC MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. KOMPOZIT LLC WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.